

AGRICUP

DIE IDEALE PNEUMATISCHE
LÖSUNG FÜR LANDMASCHINEN



710/70R38CW TECHNISCHE DATEN

GRÖSSE	RIM	APP. RIMS	LAST INDEX	STATISCHER RADIUS	FELGENART	FELGENTIEFE	SW	OD	ROLLING CIRC.
				mm		mm	mm	mm	
				in		1/32	in	in	
710/70R38CW	DW23B	DW25B	166D	850	R-1W	60	760	1940	5749
				33.5		76	29.9	76.4	226.3

GRÖSSE	FÜLLDRUCK	GESCHWINDIGKEIT, KM/H (MPH)									
		EMPFOHLENE LAST KG / LB									
		40	10	15	20	25	30	40	50	65	70
	bar	Dual	6	9	12	16	19	25	31	40	44
710/70R38CW	0.6	3390	5300	4730	4340	4180	4060	3870	3710		
	9	7470	11670	10420	9560	9210	8940	8520	8170		
	0.8	4010	6270	5600	5140	4950	4810	4580	4390	4180	3800
	12	8830	13810	12330	11320	10900	10590	10090	9670	9210	8370
	1.0	4570	7140	6380	5850	5640	5470	5210	5000	4760	4330
	15	10070	15730	14050	12890	12420	12050	11480	11010	10480	9540
	1.2	5090	7950	7100	6520	6280	6100	5800	5570	5300	4820
17	11210	17510	15640	14360	13830	13440	12780	12270	11670	10620	

GALILEOWHEEL.COM // INFO@GALILEOWHEEL.COM

UNSERE VORTEILE



HOCHWERTIGE
FLOTATION



ERHÖHTE
TRAKTION



RUHIGERES
FAHRVERHALTEN



EXTRA
LANGLEBIG



NOTLAUF
TAUGLICHKEIT



ERWEITERTER
LASTINDEX



SELBSTREINIGEND