











AGRICUP

TRACTOR BANDEN. DE VOORDELEN VAN
LUCHTBANDEN EN RUBBEREN RUPS BANDEN

GALILEO
CUPWHEEL

710/70R38CW TECHNISCHE GEGEVENS

									
MAAT	RIM	APP. RIMS	LADEN INDEX	GELADEN STATISCHE RADIO	LOOPVLAK TYPE	TREEDDIEPTE	SW	OD	RC
				mm		mm	mm	mm	
				in		1/32	in	in	
710/70R38CW	DW23B	DW25B	166D	850	R-1W	60	760	1940	5749
				33.5		76	29.9	76.4	226.3

MAAT	INFLATIED RUK	KM/H, MPH									
		AANBEVOLEN BELASTING, KG/LB									
	bar	40	10	15	20	25	30	40	50	65	70
710/70R38CW	psi	Dual	6	9	12	16	19	25	31	40	44
	0.6	3390	5300	4730	4340	4180	4060	3870	3710		
	9	7470	11670	10420	9560	9210	8940	8520	8170		
	0.8	4010	6270	5600	5140	4950	4810	4580	4390	4180	3800
	12	8830	13810	12330	11320	10900	10590	10090	9670	9210	8370
	1.0	4570	7140	6380	5850	5640	5470	5210	5000	4760	4330
15	10070	15730	14050	12890	12420	12050	11480	11010	10480	9540	

GALILEOWHEEL.COM // INFO@GALILEOWHEEL.COM

ONZE VOORDELEN



SUPERIOR
FLOTATIE



VERMINDERDE
BODEM
SAMENSTELLING



VERHOOGDE
TRACTIE



RUNDFLAT
MOGELIJKHEDEN



DUURZAAMHEID
VAN DE
ZIJWANDEN



ZELF
REINIGEN



GELIJKMATIGE
VERDELING VAN
DE BELASTING